

(12) UK Patent Application (19) GB (11) 2 354 807 (13) A

(43) Date of Printing by UK Office 04.04.2001

(21) Application No 0100566.9

(22) Date of Filing 04.06.1999

(30) Priority Data

(31) 09099542 (32) 18.06.1998 (33) US

(86) International Application Data

PCT/US99/12542 En 04.06.1999

(87) International Publication Data

WO99/66216 En 23.12.1999

(51) INT CL⁷

F16B 21/18 39/00

(52) UK CL (Edition S)

F2H HBD

(56) Documents Cited by ISA

US 4952107 A US 4930959 A US 4878795 A

US 2376089 A

(58) Field of Search by ISA

INT CL⁷ F16B 21/18 39/00

U.S.:411/107,352,353,372.5,372.6,273,999

(71) Applicant(s)

Southco Inc

(Incorporated in USA - Pennsylvania)

210 N Brinton Lake Road, Concordville,
Pennsylvania 19331, United States of America

(74) Agent and/or Address for Service

Eric Potter Clarkson

Park View House, 58 The Ropewalk, NOTTINGHAM,
NG1 5DD, United Kingdom


(72) Inventor(s)

Thomas V Aukzemas

(54) Abstract Title

Jack-out captivated screw

(57) A jack-out screw (10) for attaching a first panel (40) to a second panel (60) including a screw (20) and a housing (30) wherein the housing is mounted flush with the first panel.



GB 2 354 807 A

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F16B 21/18, 39/00	A1	(11) International Publication Number: WO 99/66216 (43) International Publication Date: 23 December 1999 (23.12.99)
(21) International Application Number: PCT/US99/12542 (22) International Filing Date: 4 June 1999 (04.06.99) (30) Priority Data: 09/099,542 18 June 1998 (18.06.98) US (71) Applicant: SOUTHCO, INC. [US/US]; 210 N. Brinton Lake Road, Concordville, PA 19331 (US). (72) Inventor: AUKZEMAS, Thomas, V.; 1106 Greenhill Avenue, Wilmington, DE 19809 (US). (74) Agents: GREENE, Gary, A. et al.; Paul & Paul, 2900 Two Thousand Market Street, Philadelphia, PA 19103 (US).		(81) Designated States: AT, AU, BR, CA, CH, CN, CZ, DE, DK, ES, FI, GB, HU, ID, IL, IN, JP, KR, LU, MX, NO, NZ, PL, PT, RU, SE, SG, SI, TR, UA, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>
(54) Title: JACK-OUT CAPTIVATED SCREW <div data-bbox="349 1239 1242 1764" data-label="Image"> </div>		
(57) Abstract <p>A jack-out screw (10) for attaching a first panel (40) to a second panel (60) including a screw (20) and a housing (30) wherein the housing is mounted flush with the first panel.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

- 1 -

JACK-OUT CAPTIVATED SCREWBACKGROUND OF THE INVENTION

5 This invention relates to fasteners in general.
More particularly, this invention relates to fasteners of
the type used to secure panels or modules to a receiving
frame or housing that requires the panel or module to be
jacked out by a screw known as a "jack-out screw."

10 Many applications exist for this type of jack-out
screw. For example, it may be advantageous to use jack-
out screws on a printed circuit board assembly that is
mounted within a housing. If that printed circuit board
assembly is plugged into a connector where there is a
15 substantial amount of force required to extract the board
from the connectors, the use of one or more jack-out
screws may be desirable.

Some prior art jacking screws use a retainer ring on
the screw shaft to captivate the screw in the housing
20 which is mounted on a first panel. This retainer ring
may separate and cause the jacking screw to uncouple or
otherwise come apart during the jacking operation. Prior
jacking screws also are not mounted flush with the top
surface of the panel on which the jacking screw is
25 retained. The present invention combines flush mounting
with a means to mount the screw in a housing that does
not use a shaft mounted retainer ring, providing a
superior jacking screw.

- 2 -

SUMMARY OF THE INVENTION

The present invention provides a captive jacking screw for attaching a first panel to a second panel. The captive jacking screw further enables the two panels to be compelled together or apart as the captive jacking screw is rotated. The captive jacking screw mounts on the first panel and is screwed into a threaded hole in the second panel.

The captive jacking screw is for attaching a first panel to a second panel when rotating the screw in a first direction and which provides a force in the axial direction of the screw with respect to the panel when the screw is rotated in the opposite direction to pry the first panel away from the second panel during rotation.

The jacking screw includes a screw and a housing where the upper surface of the housing is mountable flush with the panel on which the jacking screw is installed and an interface for securing the screw head to the housing allows for rotational movement of the screw along its axis, but does not allow for substantial axial movement of the screw with respect to the housing.

It is therefore an object of the present invention to provide a jacking screw that does not use a retainer ring which may cause the jacking screw to come apart during the jacking operation.

It is another object of the present invention to provide a jacking screw that retains the screw in its

- 3 -

housing at a location remote from the threads of the screw.

It is a further object of the present invention to provide a captive screw that does not protrude above the surface of the panel on which it is installed.

Other objects and advantages of the present invention will become apparent from the following description taken in conjunction with the accompanying drawings.

10 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front view of a jack-out captivated screw comprising a preferred embodiment of the present invention as installed on a first panel and screwed into a second panel.

15 FIG. 2 is a front view of the jack-out captivated screw of FIG. 1 as installed on a first panel midway through jack-out from a second panel.

FIG. 3 is a front view of a second embodiment of a jack-out captivated screw of the present invention.

20 FIG. 4 is a partial cutaway view of the captive screw of FIG. 3, taken along line 4--4 of FIG. 3.

FIG. 5 is a front view of a prior art jack-out captivated screw of the present invention.

25 DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now in detail to the drawings, wherein like reference numerals indicate like elements throughout

- 4 -

the several views, there is shown in FIGS. 1 and 2, a captive jacking screw 10 in accordance with one preferred embodiment of the present invention. The illustrative captive jacking screw 10 is shown generally comprising a screw 20 having a head 22 and a threaded shaft 24, a housing 30 that is mountable to a first panel 40, and a means to retain 50 the screw head 22 within the housing 30, while allowing for rotational movement of the screw 20 within the housing 30.

10 As can be seen in FIGS. 1 and 2, the screw 20 is held in place within the housing 30 such that it is free to rotate in the axial direction, however, the screw 20 is held in place within the housing 30 in the longitudinal direction by the screw retention means 50.

15 As seen in the preferred embodiment of FIGS. 1 and 2, the screw retention means 50 includes means above and below the screw head 22 to captivate the screw head 22 in the housing 30.

At the top of housing 30 is aperture 34 such that a screw driver recess 26 in screw 20 is accessible. The aperture 34 is formed by the upper part of the screw retention means 50 which includes an annular surface 33 on the housing 30 to capture the top of the screw head 22. The screw retention means further includes a washer 25 36 having a clearance hole 37 which allows the threaded shaft 24 to pass through the clearance hole 37. The washer 36 is held in place within housing 30 on annular

- 5 -

ledge 38 of housing 30. The washer 36 is placed down on annular ledge 38 and the lower edge 39 of the housing 30 is rolled over the washer 36 to secure the washer 36 and therefore the screw 20 in place.

5 The housing 30 is rigidly secured to the first panel 40 by a panel retention means. For example, as depicted in FIGS. 1 and 2, the housing 30 may be held in place by an press fit where the housing 30 is pressed into place in a hole 42 in panel 40 such that panel material flows
10 into groove 32 of housing 30.

Thus, the housing 30 is retained on panel 40 and the screw 20 is retained within the housing 30. The screw 20 is free to rotate axially, but as the screw 20 is screwed into a second panel 60 having a threaded hole 62, the
15 first panel 40 is lowered or raised as the screw 20 of the captive jacking screw 10 is rotated clockwise or counterclockwise respectively. FIG. 1 depicts the captive jacking screw 10 as mounted on a first panel 40 fully secured to a threaded hole 62 in a second panel 60.

20

FIG. 3 depicts an alternate embodiment of the captive jacking screw of the present invention. FIG. 3 shows a captive jacking screw 70 of a press-in style, but the screw 72 is installed in housing 74 from the top side
25 of housing 74 rather than the bottom side of the housing 74 as seen in FIG. 1. Here, the bottom surface of the screw head 76 sits on flat annular surface 78 of housing

- 6 -

74. Washer 80 is then placed on annular ledge 82 of housing 74 and the top 84 of the housing 74 is rolled over to secure the washer 80 and thereby the screw 72 in place to the housing 74, while allowing for rotational
5 movement of the screw 72 with respect to the housing 74.

FIGS. 3 and 4 also depict an alternate press fit connection between the housing 74 and the panel 40'. As shown in FIG. 4, the outer surface of the housing 74 is preferably knurled and is of a greater diameter than the
10 hole in the housing 74 such that there is an interference fit when the housing 74 is pressed into place in panel 40'.

FIG. 5 depicts a prior art captive screw 90 of the present invention where the screw head 92 sits above the
15 surface of the first panel 94. The housing 96 is press fit into a hole in a first panel by a panel retention means known in the art. This assembly is otherwise similar in function to that of the embodiment of FIG. 3. This prior art does not offer the advantage of being
20 flush with the surface of the panel.

Of course, any type of screw driver recess would likely work adequately for the present jack-out screw, including Phillips, Torx, slotted, and the like.

It will be recognized by those skilled in the art
25 that changes may be made in the above described embodiments of the invention without departing from the broad inventive concepts thereof. It is understood,

- 7 -

therefore, that this invention is not limited to the particular embodiments disclosed, but is intended to cover all modifications which are within the scope and spirit of the invention as defined by the appended
5 claims.

- 8 -

CLAIMS

1. A jack-out screw for attaching a first panel to a second panel when rotating the screw in a first direction and which provides a force in the axial direction of the screw with respect to the panel when the screw is rotated in the opposite direction to pry the first panel away from the second panel during rotation, comprising:

- (a) a screw having a threaded shaft and a head, said head having a top side and a bottom side; and
- (b) a housing having comprising:
 - (i) an upper surface and a perimeter edge surface, said upper surface flush with the first panel on which the jacking screw is installed;
 - (ii) a panel retention means for securing the housing to the first panel; and
 - (iii) a screw retention means for securing the screw head to the housing that allows for rotational movement of the screw along its axis, but does not allow for substantial axial movement of the screw with respect to the housing.

2. The jack-out screw of claim 1, where the panel retention means for securing the housing to the first panel is a press-in attachment means.

- 9 -

3. The jack-out screw of claim 1, where the press-in panel attachment means includes an annular groove around the perimeter edge surface of the housing.

4. The jack-out screw of claim 1, where the press-in panel attachment means includes knurling around the perimeter edge surface of the housing.

5. The jack-out screw of claim 1, where the housing installs from the top of the panel.

6. A jack-out screw for attaching a first panel to a second panel when rotating the screw in a first direction and which provides a force in the axial direction of the screw with respect to the panel when the screw is rotated in the opposite direction to pry the first panel away from the second panel during rotation, comprising:

- (a) a screw having a threaded shaft and a head, said head having a top side and a bottom side; and

- (b) a housing, comprising:

- (i) an upper surface and a perimeter edge surface, said upper surface flush with the first panel on which the jacking screw is installed;

- (ii) a panel retention means for securing the housing to the first panel; and

- 10 -

(iii) a screw retention means for securing the screw head to the housing that allows for rotational movement of the screw along its axis, but does not allow for substantial axial movement of the screw with respect to the housing, comprising an a first and a second annular surface on the housing and a washer, where the top of the screw head is retained against the first annular surface on the housing, the washer is secured to the second annular surface on the housing by a rolled over section of the housing, and the screw head is sandwiched therebetween.

7. The jack-out screw of claim 6, where the panel retention means for securing the housing to the first panel is a press-in attachment means.

8. The jack-out screw of claim 6, where the press-in panel attachment means includes an annular groove around the perimeter edge surface of the housing.

9. The jack-out screw of claim 6, where the press-in panel attachment means includes knurling around the perimeter edge surface of the housing.

- 11 -

10. The jack-out screw of claim 6, where the housing installs from the top of the panel.

11. A jack-out screw for attaching a first panel to a second panel when rotating the screw in a first direction and which provides a force in the axial direction of the screw when the screw is rotated in the opposite direction to pry the first panel away from the second panel during rotation, comprising:

- (a) a screw having a threaded shaft and a head, said head having a top side and a bottom side;
- (b) a housing, comprising:
 - (i) an upper surface and a perimeter edge surface, said upper surface flush with the first panel on which the jacking screw is installed;
 - (ii) a panel retention means for securing the housing to the first panel; and
 - (iii) a clearance hole for the screw shaft such that the screw is insertable through the hole and is held axially in position by the housing where the bottom of the screw head meets the housing; and
- (c) a washer attached to the housing for securing the top of the screw head within in the housing such that the screw head is captivated within the housing.

- 12 -

12. The jack-out screw of claim 11, where the panel retention means for securing the housing to the first panel is a press-in attachment means.

13. The jack-out screw of claim 11, where the press-in panel attachment means includes an annular groove around the perimeter edge surface of the housing.

14. The jack-out screw of claim 11, where the press-in panel attachment means includes knurling around the perimeter edge surface of the housing.

15. The jack-out screw of claim 11, where the housing installs from the top of the panel.

16. A jack-out screw for attaching a first panel to a second panel when rotating the screw in a first direction and which provides a force in the axial direction of the screw when the screw is rotated in the opposite direction to pry the first panel away from the second panel during rotation, comprising:

- (a) a screw having a threaded shaft and a head, said head having a top side and a bottom side;

- (b) a housing having an upper end and a lower end, comprising:

- (i) an upper surface and a perimeter edge

- 13 -

surface, said upper surface flush with the first panel on which the jacking screw is installed;

(ii) a panel retention means for securing the housing to the first panel; and

(iii) a clearance hole at the upper end of the housing allowing access to the screw driver recess in the screw but of a smaller diameter than the screw head, and an annular surface at the lower end of the housing for receiving a washer that has a clearance hole for the screw shaft such that the screw is insertable through the hole, where the lower end of the housing is rolled over to retain the washer against the housing whereby the screw is held axially in position by the housing;



17. The jack-out screw of claim 16, where the panel retention means for securing the housing to the first panel is a press-in attachment means.

18. The jack-out screw of claim 16, where the press-in panel attachment means includes an annular groove around the perimeter edge surface of the housing.

19. The jack-out screw of claim 16, where the press-in panel attachment means includes knurling around the perimeter edge surface of the housing.

- 14 -

20. The jack-out screw of claim 16, where the housing installs from the top of the panel.

***Fig. 1******Fig. 2***




FIG. 1A




FIG. 6




Fig. 3




Fig. 4




Fig. 5 (PRIOR ART)

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/12542

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : F16B 21/18, 39/00

US CL : 411/107, 353, 999

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 411/107, 352, 353, 372.5, 372.6, 273, 999

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ----- Y	US 2,376,089 A (SAVAGEAU) 15 May 1945 (15-05-45) entire document.	1, 2 ----- 3-5
Y	US 4,952,107 A (DUPREE) 28 August 1990 (28-08-90) see member 38.	3
Y	US 4,878,795 A (WOODROW et al.) 07 November 1989 (07-11-89) see Figs. 1-3.	4, 5
A	US 4,930,959 A (JAGELID) 05 June 1990 (05-06-90) entire document.	11-15

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

22 JULY 1999

Date of mailing of the international search report

13 AUG 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

FLEMMING SAETHER

Telephone No. (703) 308-2168